

VISIT...

LANZAROTE
Caliente.COM

AQUAPANEL®

Joint Adhesive (PU)

For AQUAPANEL® Cement Board Indoor



AQUAPANEL® Joint Adhesive (PU) is used for wall applications to bond individual AQUAPANEL® Cement Board Indoor panels. There is no need for labour-intensive coating or inserting a joint strip.

Handling and installation

Before applying the AQUAPANEL® Joint Adhesive (PU), ensure that the edges are cleaned using, for example, a wet brush. This ensures the best adhesion to the panel.

Apply a continuous linear bead of AQUAPANEL® Joint Adhesive to the edge of the already-fixed AQUAPANEL® Cement Board Indoor panel.

This must be done before the next panel is placed. Additional filling of the joint is not allowed. Place the next board onto the substructure and press against the joint adhesive (joint width approx. 1 mm). Ensure that the panels are correctly aligned horizontally and vertically and screw the board into place.

Remove any excess joint adhesive the next day using a scraper.

Coverage

approx. 50 ml/m² (approx. 25 ml/m joint)
Cartridge contents sufficient for approx. 6.5 m²

Working time

Approx. 12 minutes/m² (incl. screws)

Working temperature/climate

The material, ambient and background temperature must not fall below +8°C.

Technical data

Description	1K PUR adhesive, high viscosity
Density	1,5 g/ml
Temperature resistance	-40°C to +80°C hardened
Moisture resistance	C4 following EN12765
Open time	50 minutes (at 20°C and 65% rel. humidity)

Working safety

Wearing of protective gloves and safety glasses is recommended when handling this liquid product.

Method of delivery/storage

- 310 ml/cartridge
- Store in a dry, cool and frost-free area.
- Unopened storage life approx. 12 months

Item code: 49376